



SolidChoice MB

Specifications For SolidChoice MB Underlayment 100 sq ft Rolls



12/05

PROPERTY	SPECIFICATION
Materials	Synthetic Rubber, Polyethylene Film
Roll Size	100 Square Feet
Part Number	A19862
Fiber Color	Black
Thickness	.1"
Width	36"
Length	33'4"
Moisture Barrier	Clear 3 mil Polyethylene Film
Roll Weight	16.5lbs
Rolls Per Crate	36
Crates Per Truck Load	60
Rolls Per Truck	2,160
Water Vapor Transmission Rate	0.011 gal hour per ft ²
Density	18lbs per cubic foot

Sound Transmission Loss.

The sound-insulating property of a partition element is expressed in terms of the sound transmission loss. ASTM E90-02, ASTM E413-87

Sound Transmission Class (STC) = 52.

Impact Sound Transmission.

The method is designed to measure the impact sound transmission performance of a floor-ceiling assembly in a controlled laboratory environment. ASTM E492-96, ASTM E989-89

Impact Insulation Class (IIC) = 58.

www.solidsoundusa.com



550 Old Peachtree Road • Suwanee, Georgia • 30024 USA • 770-447-5123 • www.pliusa.com • www.solidsoundusa.com

