



## SolidChoice

Specifications For SolidChoice Underlayment 100 sq ft Rolls



02/06

PROPERTY	SPECIFICATION
Materials	Synthetic Rubber
Roll Size	100 Square Feet
Part Number	A24641
Fiber Color	Black
Thickness	.1"
Width	36"
Length	33'4"
Moisture Barrier	No
Roll Weight	16.5lbs
Rolls Per Crate	36
Crates Per Truck Load	60
Rolls Per Truck	2,160
Water Vapor Transmission Rate	0.011 g/ hour per ft <sup>2</sup>
Density	18lbs per cubic foot

### Sound Transmission Loss.

The sound-insulating property of a partition element is expressed in terms of the sound transmission loss. ASTM E90-02, ASTM E413-87  
**Sound Transmission Class (STC) = 52.**

### Impact Sound Transmission.

The method is designed to measure the impact sound transmission performance of a floor-ceiling assembly in a controlled laboratory environment. ASTM E492-90, ASTM E989-89  
**Impact Insulation Class (IIC) = 58.**

[www.solidsoundusa.com](http://www.solidsoundusa.com)



550 Old Peachtree Road • Suwanee, Georgia • 30024 USA • 770-447-5123 • [www.pliusa.com](http://www.pliusa.com) • [www.solidsoundusa.com](http://www.solidsoundusa.com)

