



SolidWalk LT

SolidWalk LT Underlayment (2 mil Film, Lip and Tape) 100 sq ft Rolls



06/07

PROPERTY	SPECIFICATION
Materials	Synthetic Fiber Blend, Polyethylene Film, Tape
Roll Size	100 square Feet
Part Number	A19846
Fiber Color	Blue/Grey
Density	20.0 oz/sq yd (2.22oz/sq ft)
Thickness	.125 / 1/8"
Width	36"
Length	33'4"
Weight Per Roll	16 lbs
Rolls Per Crate	28
Crates Per Truck	60
Rolls Per Truck	1,680
Antimicrobial	Yes
Moisture Barrier	Blue 2 mil Polyethylene Film
Lip	Extended 3" Beyond Fiber Pad Material
Tape	Included On Film Opposite Lip Side
Solid Sound Logo	Printed On Film
Flammability	California Technical Bulletin 117, Section D Part I & Section C part v paragraph 2.
R-Value	@0.125" = 0.52 hr-ft ² °F/Btu (4.19/inch)
Moisture Statement.	Solid Sound™ Fiber Pad will absorb and allow dispersion throughout the product of water moisture in accumulations not exceeding one gallon per 24 hrs per 300 square feet of product and/or allowed to continue to accumulate for more than 7 days.

Sound Transmission Loss.

The sound-insulating property of a partition element is expressed in terms of the sound transmission loss.

ASTM E90-97, ASTM E413-87

Sound Transmission Class (STC) = 54.

Impact Sound Transmission.

The method is designed to measure the impact sound transmission performance of a floor-ceiling assembly in a controlled laboratory environment.

ASTM E492-90, ASTM E989-89

Impact Insulation Class (IIC) = 58.

www.solidsoundusa.com



550 Old Peachtree Road • Suwanee, Georgia • 30024 USA • 770-447-5123 • www.pliusa.com • www.solidsoundusa.com

